

Firmamento

Description	Phosphorescent pigment based transparent finish INTERIOR
Support surface	Traditional or pre-mixed plaster, gypsum boards
Composition	Water dispersion with organic ligand

Technical Characteristics

Specific Weight	1,30 ± 0,02 Kg/L
pH	8,5
Yield	11-12 m ² /L for each coat
Dry to touch	5-6 h at 20 °C RU 60%

Application

Environmental conditions	T. min 5 °C T.max 30 °C R.U. 60%
Tools	Sponge or Brush
Dilution	Ready to use
Colours	Transparent
Advices	Always apply in the recommended condition. Verify the support status before beginning and check that the surfaces is clean, dry and with uniform absorption.

APPLICATION FIRMAMENTO:

Apply Firmamento in one or two coats, depending on the desired intensity, with the indicated sponge or with a brush. To highlight the materic draw, wash the smooth surface immediately after with a clean wet sponge in order to keep the product only in the cavity. Once applied, Firmamento can be protected with Trasparenti

Packaging:

Firmamento: 1,0 Lt

Waste treatment methods: European Waste Catalogue code (Decision 2014/955/UE) 15 01 02. The EWC code indicated is only a general indication, based on the original composition of the product and its intended use. The user has the final responsibility to choose the most appropriate EWC code, based on the actual use of the product, and any alterations or contaminations.

Storage: Minimum Temperature: 5 °C

Maximum Temperature: 30 °C

Stability:

360 days in the original cans.

F.D.A. s.r.l.

24043 Caravaggio / BG

Via Piave,1

Tel. e Fax +39 035 578 51 39 info@firmadautore.it

The above technical information is the result of accurate laboratory tests and practical experience. However, given that the product is often used without our control, we cannot but guarantee its quality. This information is subject to possible updates by the company.