

Galassie

Description	Transparent acrylic water-based decorative finish with sanded effect INTERIOR
Support surface	Traditional or pre-mixed plaster, gypsum boards
Composition	Water dispersion with organic binder and pearlescent pigment
Technical Characteristics	
Specific Weight	1,23 ± 0,03 Kg/L
pH	8,5
Yield	8/10 m ² /L for each coat
Dry to touch	4-6 h at 20 °C RU 60%
Application	
Environmental conditions	T. min 5 °C T.max 30 °C R.U. 60%
Tools	Spalter
Dilution	Ready to Use
Colours	Luna (Silver), Sole (Gold), Aria and Oceano (iridescent)
Advices	Always apply in the recommended condition. Verify the support status before beginning and check that the surfaces is clean, dry and with uniform absorption. Before apply two coats of Fondo FDA Fine.

APPLICATION OF SABBIA:

Apply Galassie in the chosen colour in a single coat using a flat decorative brush in cross strokes on the surfaces previously prepared with Fondo FDA fine, taking care to avoid distinct rectangular patterns. In order to obtain a softer effect and so as to distribute the product more evenly, go over the surface again using a dry brush. The quantity of paint used, the size of the surface, the form and the intensity of the brush strokes all determine the personalized decorative effect achieved.

Packaging:

Galassie: 2,5 Lt and 1,0 Lt

Waste treatment methods:

Empty Can: special waste similar to urban waste

Can with residue: special waste

Storage: Minimum Temperature: 5 °C

Maximum Temperature: 30 °C

Stability:

360 days in the original cans.

F.D.A. s.r.l.

24043 Caravaggio / BG

Via Piave,1

Tel. e Fax +39 035 578 51 39 info@firmadautore.it

The above technical information is the result of accurate laboratory tests and practical experience. However, given that the product is often used without our control, we cannot but guarantee its quality. This information is subject to possible updates by the company.