

# Lucido

Description	Protective poliuretanic transparent finish with high gloss INTERIOR
Support surface	Traditional or pre-mixed plaster, gypsum boards
Composition	Water dispersion with poliuretanic binder
<b>Technical Characteristics</b>	
Specific Weight	1,00 ± 0,03 Kg/L
pH	8,5
Yield	11/12 m <sup>2</sup> /L for each coat
Dry to touch	5-6 h at 20 °C RU 60%
<b>Application</b>	
Environmental conditions	T. min 5 °C T.max 30 °C R.U. 60%
Tools	Brush, Sponge or Sponge roll
Dilution	Ready to Use
Colours	Transparent
Advices	Always apply in the recommended condition. Verify the support status before beginning and check that the surfaces is clean, dry and with uniform absorption.

## APPLICATION LUCIDO:

Apply the first coat of Lucido with the recommended sponge, in case of an irregular surface, otherwise with a brush or roll. After 5-6 hours apply a second coat with brush or roll.

## Packaging:

Lucido: 1,0 Lt

**Waste treatment methods:** European Waste Catalogue code (Decision 2014/955/UE) 15 01 02. The EWC code indicated is only a general indication, based on the original composition of the product and its intended use. The user has the final responsibility to choose the most appropriate EWC code, based on the actual use of the product, and any alterations or contaminations.

**Storage:** Minimum Temperature: 5 °C  
Maximum Temperature: 30 °C

**Stability:**  
360 days in the original cans