

# Marmorino Effetto Antico

Description	Decorative product based on slaked lime with fine granulometry INTERIOR
Support surface	Traditional or pre-mixed plaster, gypsum boards
Composition	Water dispersion based on organic binder and slaked lime
<b>Technical Characteristics</b>	
Specific Weight	1,7 ± 0,02 Kg/L
pH	<12
Yield	0,8/1,0 m <sup>2</sup> /Kg for each coat
Dry to touch	10-12 h at 20 °C RU 60%
<b>Application</b>	
Environmental conditions	T. min 5 °C T.max 30 °C R.U. 65%
Tools	INOX Spatula and sponge float
Dilution	Ready to Use
Colours	White, Colour chart Calce Firma d'Autore
Advices	Always apply in the recommended condition. Verify the support status before beginning and check that the surfaces is clean, dry and with uniform absorption. Before apply one coat of Fondo FDA Medio.

## APPLICATION Marmorino Effetto Antico:

Spread a coat of Marmorino Effetto Antico FDA in the chosen colour using a stainless steel spatula, being careful to leave an even thickness, and finish with the Sponge Flota. After 8 h apply a second coat with steel spatula and finishing with the Sponge Float, then smooth the whole surface with the stainless steel spatula to obtain the antique effect. Always work in full the walls, in order to avoid unaesthetic differences of color.

"Cera d'Api" (bee's wax) can be applied on the finish after at least 48 hours by rubbing a thin layer of over the whole surface using a sponge, until it is completely absorbed avoiding excessive accumulations of material. After 5/10 minutes proceed with polishing using a non-abrasive soft cloth (microfiber, cotton or linen).

## Packaging:

Marmorino Effetto Antico: 20 Kg and 8 Kg

## Waste treatment methods:

Empty Can: special waste similar to urban waste

Can with residue: special waste

**Storage:** Minimum Temperature: 5 °C

Maximum Temperature: 30 °C

**Stability:**

360 days in the original cans.

F.D.A. s.r.l.

24043 Caravaggio / BG

Via Piave,1

Tel. e Fax +39 035 578 51 39 [info@firmadautore.it](mailto:info@firmadautore.it)

The above technical information is the result of accurate laboratory tests and practical experience. However, given that the product is often used without our control, we cannot but guarantee its quality. This information is subject to possible updates by the company.