

Primer FDA

Description	Transparent fixative water base with high penetration INTERIOR
Support surface	Traditional or pre-mixed plaster, gypsum boards
Composition	Water dispersion with acrylic binder
Technical Characteristics	
Aspect	Transparent
Specific Weight	1,00 ± 0,03 Kg/L
pH	8,5
Yield	10/12 m ² /L for each coat
Dry to touch	6-8 h at 20 °C RU 60%
Application	
Environmental conditions	T. min 5 °C T.max 30 °C R.U. 60%
Tools	Brush
Dilution	Diluted 1:5 with water
Colours	Colourless
Advices	All surfaces must be dry, clean thoroughly, in uniform absorption and appearance. Remove the old paints without good adhesion and flaking parts.

Packaging:

Primer FDA: 5,0 Lt and 1,0 Lt

Waste treatment methods:

Empty Can: special waste similar to urban waste

Can with residue: special waste

Storage: Minimum Temperature: 5 °C

Maximum Temperature: 30 °C

Stability:

360 days in the original cans.

F.D.A. s.r.l.

24043 Caravaggio / BG

Via Piave,1

Tel. e Fax +39 035 578 51 39 info@firmadautore.it

The above technical information is the result of accurate laboratory tests and practical experience. However, given that the product is often used without our control, we cannot but guarantee its quality. This information is subject to possible updates by the company.