

Satin Soft

Description	Semi-gloss finish with chamois effect INTERIOR
Support surface	Traditional or pre-mixed plaster, gypsum boards
Composition	Water dispersion with organic binder and pearlescent pigment
Technical Characteristics	
Specific Weight	1,0 ± 0,03 Kg/L
pH	8,5
Yield	10/12 m ² /L for each coat
Dry to touch	3-4 h at 20 °C RU 60%
Application	
Environmental conditions	T. min 5 °C T.max 30 °C R.U. 60%
Tools	Spalter or Effetto Trama Brush
Dilution	Ready to Use
Colours	Colour chart Satin & Satin Soft Firma d'Autore
Advices	Always apply in the recommended condition. Verify the support status before beginning and check that the surfaces is clean, dry and with uniform absorption. Before apply one coat of Fondo FDA Fine.

APPLICATION SATIN SOFT:

Apply Satin Soft in irregular cross brush strokes across the surface which has been previously prepared using Fondo FDA fine. It is important to avoid distinct rectangular patterns. When the first coat is dry after 4-6 hours apply a second coat in the same way. In order to obtain a softer-edged effect and render the distribution of the product more homogeneous, go over the surface again with a dry brush. The quantity of the material used, the dimension, the form and intensity of the brush strokes all determine the personalized decorative effect achieved.

APPLICATION SATIN SOFT effetto tela (fabric effect):

Apply Satin Soft using irregular cross brush strokes on the surface which has been previously prepared using Fondo FDA fine. As soon as the application is completed, go over the surface again with the Effetto Trama brush using horizontal strokes. After the first coat has dried (4-6 hours), apply a second coat in the same way but go over the surface using the Effetto Trama brush this time using vertical strokes. The quantity of material used, the dimension, the form and the intensity of the brush strokes, all determine the personalized decorative effect.

Packaging:

Satin Soft: 5,0 Lt, 2,5 Lt and 1,0 Lt

Waste treatment methods:

Empty Can: special waste similar to urban waste

Can with residue: special waste

Storage: Minimum Temperature: 5 °C

Maximum Temperature: 30 °C

Stability:

360 days in the original cans.

F.D.A. s.r.l.

24043 Caravaggio / BG

Via Piave,1

Tel. e Fax +39 035 578 51 39 info@firmadautore.it

The above technical information is the result of accurate laboratory tests and practical experience. However, given that the product is often used without our control, we cannot but guarantee its quality. This information is subject to possible updates by the company.