

Velluto

Description	Pearly decorative finish with velvet effect white or black INTERIOR
Support surface	Traditional or pre-mixed plaster, gypsum boards
Composition	Water dispersion with organic binder and pearlescent pigment
Technical Characteristics	
Specific Weight	1,0 ± 0,03 Kg/L
pH	8,5
Yield	9/11 m ² /L for each coat
Dry to touch	3-4 h at 20 °C RU 60%
Application	
Environmental conditions	T. min 5 °C T.max 30 °C R.U. 60%
Tools	Spalter, Plastic Spatula
Dilution	Ready to Use
Colours	Colour chart Bianco e Nero Soft Firma d'Autore
Advices	Always apply in the recommended condition. Verify the support status before beginning and check that the surfaces is clean, dry and with uniform absorption. Before apply one coat of Fondo FDA Fine.

APPLICATION OF VELLUTO:

Apply the Velluto product in irregular cross-brush strokes on the surface which has been prepared with Fondo FDA fine. It is important to avoid distinct rectangular patterns. When the first coat has dried after 4-6 hours, apply a second coat in the same way. Wait for a few minutes (5-10) then flatten the creases with a plastic spatula. The quantity of material employed, the dimensions, the form and the intensity of the brush strokes all determine the personalized decorative effect achieved.

Packaging:

Velluto: 2,5 Lt and 1,0 Lt

Stability:

360 days in the original cans.

Waste treatment methods:

Empty Can: special waste similar to urban waste

Can with residue: special waste

Storage: Minimum Temperature: 5 °C

Maximum Temperature: 30 °C

F.D.A. s.r.l.

24043 Caravaggio / BG

Via Piave,1

Tel. e Fax +39 035 578 51 39 info@firmadautore.it

The above technical information is the result of accurate laboratory tests and practical experience. However, given that the product is often used without our control, we cannot but guarantee its quality. This information is subject to possible updates by the company.